

CONVEY-ALL™

Conveyor System



ADVANTAGES

- Safely convey substrates or stock made from a wide range of materials
- Infinitely variable solid-state belt speed control compatible with numerous industrial applications
- Specialized belt types available for your specific application
- Digital belt speed readout for precise tracking
- Easy to set up and use
- Options and accessories available for countless printing applications

AWT's Convey-All™ conveyor systems are engineered for high-quality, high-speed production. The chassis is constructed of tough, solid steel and the premium quality Fiberlon™ belt is strong and durable.

These versatile systems are ideal for conveying paper, posterboard, plastics, glass, composites, wood, metal, bottles, cans, sheets, carpet, medical products, and thousands of other materials.

Convey-All systems feature easily-adjustable solid-state belt speed controls. Standard conveyor length is 10' long with widths of 24" (61cm), 36" (91cm) 48" (122cm), 60" (152cm) and 72" (183cm). Larger sizes are available in any length.


The optional vacuum holddown and exhaust system firmly holds each substrate on the belt, preventing it from rolling over, while simultaneously venting exhaust fumes as needed. Optional belt-and-roller systems are available for use with glass and other sensitive substrates.




 4321 N. Knox Ave., Chicago IL, 60641

 www.awt-gpi.com

 sales@awtworldtrade.com

 773.777.7100

 773.777.0909

CONVEY-ALL™

Safely convey a wide range of substrates, stock, or parts

Standard Features

- Solid-state, variable belt speed control
- Easily adjustable production controls with digital readout of exact belt speed
- Durable, heat-resistant Fiberlon™ belt
- Custom lengths available
- Easy installation; simply plug into a standard 115V AC, single-phase outlet
- Heavy-duty steel construction

Options and Accessories

- Custom widths available
- Hundreds of other belt types
- Custom conveyor angles
- Vacuum holddown system
- Vacuum exhaust system
- Additional conveyor length – 2 to 100 feet
- Additional conveyor height
- Higher or lower belt speeds
- Servo drive
- Other voltages available

Specifications

MODEL NO.	DESCRIPTION	CONVEYOR WIDTH	CONVEYOR LENGTH
CNV-12	Conveyor, with Steel & Fiberlon Belt	12"W	10'L
CNV-24	Conveyor, with Steel & Fiberlon Belt	24"W	10'L
CNV-36	Conveyor, with Steel & Fiberlon Belt	36"W	10'L
CNV-48	Conveyor, with Steel & Fiberlon Belt	48"W	10'L
CNV-60	Conveyor, with Steel & Fiberlon Belt	60"W	10'L
CNV-72	Conveyor, with Steel & Fiberlon Belt	72"W	10'L
CNV-80	Conveyor, with Steel & Fiberlon Belt	80"W	10'L
CNV-100	Conveyor, with Steel & Fiberlon Belt	100"W	10'L

©2021 AWT World Trade Inc. No part of this literature may be reproduced without written permission. Specifications subject to change without notice. #LIT-1099 11/24/21

THE AWT WORLD TRADE GROUP

Combining state-of-the art engineering expertise and creativity with outstanding customer service to provide quality, consistency, and value to the screen printing industry for more than 40 years



AWT
World Trade Inc.
awt-gpi.com



GRAPHIC PARTS
INTERNATIONAL INC.
gpiparts.com



GENERAL CYLINDER PRESSES
generalcylinderpresses.com



Saturn
Rack™
saturnrack.com



American
screenprintmachinery.com

A Company with
proven experience.



AWT
World Trade Inc.

Products
you can trust.