

# CURE-TEX™

*Moving Ahead  
With Technology*

## The Economical Approach to Plastisol Curing



**Cure-Tex 2**  
Optional Dual Heat Chamber

### ADVANTAGES

- Air flow for uniform heat distribution
- Easy heat panel height adjustment
- Quick gate height adjustment for thicker garments
- Energy efficient, low cost operation
- Small footprint; requires little floor space
- Easy to set-up and operate

**NEW!**

The Cure-Tex line now includes the compact and economical 16-inch model using standard household current. Perfect for short runs, smaller operations or wherever space is at a premium.

A consistent leader in the economy class of textile dryers, the Cure-Tex™ features the same high quality components as our larger infrared units at an entry level price.

Engineered for top production speeds, the Cure-Tex can handle up to twelve dozen garments per hour, or twenty dozen caps per hour when equipped with the unit's optional cap dryer panel. The Cure-Tex™2 features an optional dual heat chamber with an increased belt length for garments with extended curing requirements.

In both units, solid state temperature controls and heavy-duty chamber insulation combine for an efficient means of curing that keeps heat in and reduces energy consumption. Heat is delivered efficiently and uniformly to the garment through a top-down airflow pattern that guards against scorching.



**A.W.T. World Trade Inc.**  
A Division of The A.W.T. World Trade Group

4321 N. Knox Avenue • Chicago, IL 60641 USA

773.777.7100 • Fax: 773.777.0909

sales@awt-gpi.com • www.awt-gpi.com

# Cure-Tex™ Textile Dryer

## Low-cost plastisol curing

A user friendly control panel provides complete up-front operation with independent settings for temperature and belt speed. Heat panel height is easily adjusted, and a rugged Fiberlon™ belt withstands heat up to 500°F (260°C).

Designed for easy access to all components and built to last, both units provide long life with minimal service. Options include a digital temperature control, extra conveyor lengths by the foot, and a handy storage shelf.

### Standard Features

- Solid state temperature controls
- Heavy-duty chamber insulation
- Variable speed conveyor drive
- Fiberlon™ conveyor belt
- Adjustable chamber doors
- Forced-air, top-down airflow
- Adjustable radiant heat panel

### Options and Accessories

- Cap drying panel for some units
- Additional conveyor sections
- 50 Hz conversion
- Dual chamber for most models

### Specifications: Cure-Tex

Cat. No.	Belt Width	Infeed	Heat Chamber	Outfeed	Electrical	Amps
CT-16-60	16" (41 cm)	15" (38 cm)	28" (71 cm)	15" (38 cm)	115 V,1Ph, 60 Hz	14.5
CT-16-50	16" (41 cm)	15" (38 cm)	28" (71 cm)	15" (38 cm)	230 V,1Ph, 50 Hz	8
CT-18-50 <sup>*1</sup>	18" (46 cm)	15" (38 cm)	28" (71 cm)	15" (38 cm)	208-240/1Ph, 50 Hz	18
CT-18-60 <sup>*1</sup>	18" (46 cm)	15" (38 cm)	28" (71 cm)	15" (38 cm)	208-240/1Ph, 60 Hz	18
CT-24-50 <sup>*2</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	208-240/1Ph, 50 Hz	22
CT-24-60 <sup>*2</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	208-240/1Ph, 60 Hz	22
CT-24-380 <sup>*2</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	380-415/3Ph, 50 Hz	12
CTC-24-50 <sup>*3</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	208-240/1Ph, 50 Hz	44
CTC-24-60 <sup>*3</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	208-240/1Ph, 60 Hz	44
CTC-24-380 <sup>*3</sup>	24" (61 cm)	24" (61 cm)	36" (91 cm)	24" (61 cm)	380-415/3Ph, 50 Hz	24

### Specifications: Cure-Tex 2

Cat. No.	Belt Width	Infeed	Heat Chamber	Outfeed	Electrical	Amps
CT-18-50D <sup>*1</sup>	18" (46 cm)	15" (38 cm)	56" (142 cm)	15" (38 cm)	208-240/1Ph, 50 Hz	36
CT-18-60D <sup>*1</sup>	18" (46 cm)	15" (38 cm)	56" (142 cm)	15" (38 cm)	208-240/1Ph, 60 Hz	36
CT-24-50D <sup>*1</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	208-240/1Ph, 50 Hz	44
CT-24-60D <sup>*2</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	208-240/1Ph, 60 Hz	44
CT-24-380D <sup>*2</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	380-415/3Ph, 50 Hz	24
CTC-24-50D <sup>*3</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	208-240/1Ph, 50 Hz	44
CTC-24-60D <sup>*3</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	208-240/1Ph, 60 Hz	44
CTC-24-380D <sup>*3</sup>	24" (61 cm)	24" (61 cm)	72" (183 cm)	24" (61 cm)	380-415/3Ph, 50 Hz	24

\*1 Unit not available with cap dryer panel

\*2 Unit available with cap dryer panel retrofit

\*3 Unit has cap dryer panel as standard equipment



**A.W.T. World Trade Inc.**  
A Division of The A.W.T. World Trade Group

4321 N. Knox Avenue • Chicago, IL 60641 USA

773.777.7100 • Fax: 773.777.0909

sales@awt-gpi.com • www.awt-gpi.com